

Technical data

Rated voltage	120V AC
Input voltage range	110-120V AC
Driver output	-
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	No
Source	E26
Color temperature real output	-
Real light output	- lm
Total consumption	- W
Energy class	-
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Cooper

catalogue 2024 p. 18

ref. GL179007113

EAN. 3663660255882

Model 4



Materials and finishes

Material	aluminium
Colour	Velvet black - 113

Logistic data

Product dimensions	H.2485 L.305 P.482
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.270 L.270 P.2500
Package dimensions 1	H.510 L.360 P.260

Certifications and warranties

CE	No
UL	Yes
EAC	No
RoHS	No
ENEC	No
Anti-corrosion	25 years (on Aluminum)
Technical	5 years
Electronics	5 years