

Technical data

Rated voltage	120V AC
Input voltage range	110-120V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Clear polycarbonate
Bulb cover	-
Source	E26
Color temperature real output	-
Real light output	- lm
Total consupction	- W
Standby power	-
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Victoria

catalogue 2024 p. 64

ref. PE164003000

EAN. 3663660295864

Model 3



Materials and finishes

Material	aluminium
Colour	Jet black - 000

Logistic data

Product dimensions	H.694 L.275 P.402
Net weight	2.120 Kg
Gross weight	3.630 Kg
Package dimensions 1	H.640 L.430 P.260

Certifications and warranties

CE	No
UL	Yes
EAC	No
RoHS	No
ENEC	No
Anti-corrosion	25 years (on Aluminum)
Technical	5 years
Electronics	5 years